

**6'-15000 Double-Wall Compartment Tank Extension
15077 (liters)**

Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)
0.5	15	25.5	1332	50.5	3461	75.5	5951
1.0	25	26.0	1369	51.0	3508	76.0	6003
1.5	36	26.5	1407	51.5	3556	76.5	6055
2.0	48	27.0	1444	52.0	3603	77.0	6107
2.5	62	27.5	1482	52.5	3651	77.5	6159
3.0	76	28.0	1520	53.0	3698	78.0	6210
3.5	91	28.5	1558	53.5	3746	78.5	6262
4.0	108	29.0	1597	54.0	3794	79.0	6314
4.5	125	29.5	1636	54.5	3842	79.5	6366
5.0	143	30.0	1675	55.0	3891	80.0	6419
5.5	162	30.5	1714	55.5	3939	80.5	6471
6.0	181	31.0	1754	56.0	3987	81.0	6523
6.5	201	31.5	1794	56.5	4036	81.5	6575
7.0	222	32.0	1834	57.0	4085	82.0	6627
7.5	244	32.5	1874	57.5	4134	82.5	6679
8.0	266	33.0	1915	58.0	4183	83.0	6732
8.5	289	33.5	1956	58.5	4232	83.5	6784
9.0	312	34.0	1997	59.0	4281	84.0	6836
9.5	336	34.5	2038	59.5	4330	84.5	6889
10.0	360	35.0	2079	60.0	4379	85.0	6941
10.5	385	35.5	2121	60.5	4429	85.5	6993
11.0	411	36.0	2163	61.0	4478	86.0	7046
11.5	437	36.5	2205	61.5	4528	86.5	7098
12.0	463	37.0	2248	62.0	4578	87.0	7150
12.5	490	37.5	2290	62.5	4628	87.5	7203
13.0	518	38.0	2333	63.0	4678	88.0	7255
13.5	546	38.5	2376	63.5	4728	88.5	7308
14.0	574	39.0	2419	64.0	4778	89.0	7360
14.5	603	39.5	2463	64.5	4828	89.5	7413
15.0	632	40.0	2506	65.0	4878	90.0	7465
15.5	662	40.5	2550	65.5	4929	90.5	7518
16.0	692	41.0	2594	66.0	4979	91.0	7570
16.5	722	41.5	2638	66.5	5030	91.5	7622
17.0	753	42.0	2682	67.0	5080	92.0	7675
17.5	784	42.5	2727	67.5	5131	92.5	7727
18.0	816	43.0	2771	68.0	5182	93.0	7780
18.5	848	43.5	2816	68.5	5233	93.5	7832
19.0	880	44.0	2861	69.0	5284	94.0	7885
19.5	913	44.5	2906	69.5	5335	94.5	7937
20.0	946	45.0	2952	70.0	5386	95.0	7989
20.5	980	45.5	2997	70.5	5437	95.5	8042
21.0	1014	46.0	3043	71.0	5488	96.0	8094
21.5	1048	46.5	3089	71.5	5539	96.5	8147
22.0	1082	47.0	3135	72.0	5590	97.0	8199
22.5	1117	47.5	3181	72.5	5642	97.5	8251
23.0	1152	48.0	3227	73.0	5693	98.0	8304
23.5	1188	48.5	3274	73.5	5745	98.5	8356
24.0	1223	49.0	3320	74.0	5796	99.0	8408
24.5	1259	49.5	3367	74.5	5848	99.5	8460
25.0	1296	50.0	3414	75.0	5900	100.0	8512

**6'-15000 Double-Wall Compartment Tank Extension
15077 (liters)**

Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)	Liquid Depth (cm)	Volume (liters)
100.5	8565	125.5	11099	150.5	13331	175.5	14901
101.0	8617	126.0	11148	151.0	13371	176.0	14920
101.5	8669	126.5	11196	151.5	13410	176.5	14939
102.0	8721	127.0	11244	152.0	13449	177.0	14956
102.5	8773	127.5	11292	152.5	13488	177.5	14973
103.0	8825	128.0	11340	153.0	13527	178.0	14990
103.5	8877	128.5	11388	153.5	13565	178.5	15005
104.0	8929	129.0	11436	154.0	13603	179.0	15019
104.5	8981	129.5	11483	154.5	13641	179.5	15032
105.0	9033	130.0	11531	155.0	13678	180.0	15044
105.5	9084	130.5	11578	155.5	13715	180.5	15055
106.0	9136	131.0	11625	156.0	13752	181.0	15064
106.5	9188	131.5	11672	156.5	13789	181.5	15072
107.0	9239	132.0	11719	157.0	13825	182.0	15077
107.5	9291	132.5	11766	157.5	13861		
108.0	9343	133.0	11813	158.0	13897		
108.5	9394	133.5	11859	158.5	13932		
109.0	9445	134.0	11905	159.0	13967		
109.5	9497	134.5	11951	159.5	14002		
110.0	9548	135.0	11997	160.0	14037		
110.5	9599	135.5	12043	160.5	14071		
111.0	9651	136.0	12089	161.0	14104		
111.5	9702	136.5	12134	161.5	14138		
112.0	9753	137.0	12180	162.0	14171		
112.5	9804	137.5	12225	162.5	14204		
113.0	9855	138.0	12270	163.0	14236		
113.5	9905	138.5	12315	163.5	14268		
114.0	9956	139.0	12359	164.0	14299		
114.5	10007	139.5	12404	164.5	14331		
115.0	10057	140.0	12448	165.0	14361		
115.5	10108	140.5	12492	165.5	14392		
116.0	10158	141.0	12536	166.0	14422		
116.5	10209	141.5	12580	166.5	14451		
117.0	10259	142.0	12623	167.0	14481		
117.5	10309	142.5	12667	167.5	14509		
118.0	10359	143.0	12710	168.0	14538		
118.5	10409	143.5	12753	168.5	14565		
119.0	10459	144.0	12796	169.0	14593		
119.5	10509	144.5	12838	169.5	14620		
120.0	10559	145.0	12880	170.0	14646		
120.5	10609	145.5	12923	170.5	14672		
121.0	10658	146.0	12964	171.0	14698		
121.5	10708	146.5	13006	171.5	14722		
122.0	10757	147.0	13048	172.0	14747		
122.5	10806	147.5	13089	172.5	14771		
123.0	10855	148.0	13130	173.0	14794		
123.5	10904	148.5	13171	173.5	14816		
124.0	10953	149.0	13211	174.0	14838		
124.5	11002	149.5	13251	174.5	14860		
125.0	11051	150.0	13292	175.0	14881		

6'-15000 Double-Wall Compartment Tank Extension 15077 (liters)



CONTAINMENT
S O L U T I O N S®

HOW TO PROPERLY GAUGE YOUR TANK:

Underground storage tanks require periodic measurement to determine current inventory level. Using the proper methods when gauging your tank's contents will insure the most accurate reading and insure that you do not damage your tank. The following procedure should be followed whenever you use a gauge stick to determine the amount of product that is in your tank:

- 1) Use a wood dipstick with a rubber or nylon tip. Metallic dipsticks are not recommended. This will insure that frequent tank gaugings or an accidental dropping of the gauge stick into the tank will not damage the tank bottom.
- 2) Slowly lower your gauge stick into the fill port until it touches the tank bottom. Never free drop the gauge stick. This can result in inaccurate measurements due to product splashing. Free dropping can also result in gauge stick damage and tank damage.
- 3) Remove your dipstick slowly and read the product level directly from the gauge stick.

Water Paste Detection:

To detect water in the tank bottom, water detection paste is available from petroleum equipment distributors. See vendor below or suitable equal.

Gasoil Water Finding Paste
Federal Process Corp.
800-846-7325
www.gasoila.com

Caution

Pressurized deliveries are not recommended. If the delivery vehicle uses pumps to fill the tank, install overfill shutoff equipment in the tank and truck to prevent the tank from being overfilled. **Overfilling the tank under pressure will damage the tank even if the tank vent is unrestricted.**

Containment Solutions, Inc.
333 North Rivershire Dr., Suite 190
Conroe, TX 77304
Tel: 936-756-7731
Fax: 936-756-7766

Note: Calibration chart is based on the fluid level above a 8mm [5/16"] deflector plate.